

Model	ER 3600SLV
Device	Disposable Filtering Face Piece
Class	FFP3 NR
Approval	EN 149:2001+A1:2009 SGS (CE0598)



Unit	Inhalation Resistance*	Inhalation Resistance*	Exhalation Resistance*	NaCl Initial Penetration	Oil Initial Penetration	Classification
Condition	@30 L/min	@95 L/min	@160 L/min	@ 95L/min	@ 95L/min	EN 149:2001+A1:2009 FFP3 NR
Limit	< 1 mbar	< 3 mbar	< 3 mbar	< 1%	< 1%	Usage level Up to 30 x OEL

FEATURES


Nose Clip: Maintains its features even after repeated usage. Perfect position of the clip avoids risk of rupture or dislocation.

Thermal Bonding Layer: Provides resistance to deformation and collapse due to perspiration-related problems by making the mask sturdier.

Head Band: Extremely comfortable with an ideal balance between flexibility and snug fit. Will not lose flexibility or fit in hot or cold working conditions thereby proving its durability.

Exhalation Valve: Perfectly designed Exhalation valve provides breathing comfort to the wearer.

Compatibility: Suitable for use with other Personal Protective Equipment such as helmets, safety glasses and ear protection.



Mfd. under license from:

EyeveX Safety U.S.A., Inc. 1013 Centre Road, Suite 403-B, Wilmington, DE 19805, U.S.A.

www.eyevexsafety.com

MATERIALS

Band	Latex-free Head bands
Nose clip	Double core galvanized steel wire coated with plastic material
Layers	Electrostatic polypropylene melt blown, polypropylene non-woven fabric
Exhalation valve	Polypropylene Exhalation valve in Red color
Weight	11gm ± 5%

PACKAGING INFORMATION

Model	Pouch (pcs)	Inner Box (pcs)	Outer Box (pcs)	Box Sizes (cm)	Carton Weight (kg)
ER 3600SLV	1	25	1000	Inner box 150*120*200 mm Big Carton box 770*500*470.5 mm	13.24

PRE-USE INSTRUCTIONS

- Wash your hands thoroughly.
- Read the instructions carefully before use.
- Check the 'end of shelf life' date. Discard if the date has passed.
- Check for any damage.
- Check if the mask is suitable for the purpose.
- The part with the nose clip should be towards top when putting on the mask.

USER INSTRUCTIONS



1. Hold the mask on your face keeping the head bands on the outer side.



3. Extend the mask to cover your mouth and chin. Press the nose clip to fit the shape of nose.



2. Pull the both the headbands over the top of the head. Place the upper band on the head. Place the lower band behind The neck.



4. Check the fit and eliminate leakage if any. Dispose of used masks.

IMPORTANT NOTE: The wearer must go through training to understand the proper use of the product. Change mask immediately if breathing becomes difficult or mask gets damaged or distorted, or a proper face fit cannot be maintained. Careful observance and practice of these instructions is crucial in safe mask use.

FIT CHECK




- Check for any air leaks by covering the front of the mask with both hands. Be careful not to disturb the fitting.
- In case of leak, re-adjust the nose clip and the bands, and re-check for leaks with both hands.
- If you CANNOT achieve a proper fit, DO NOT enter a hazardous area. Seek help from your supervisor.
- Users should be fit tested in accordance with national requirements.

WARNINGS AND USE LIMITATIONS

1. Failure to follow all the instructions on the use of this product could reduce the effectiveness of mask.
2. A properly selected mask is essential to protect your health. Before using this mask, consult an Industrial Hygienist or Occupational Safety Professional to determine the suitability of the mask for your intended use.
3. This product does not supply oxygen. Use only in adequately ventilated areas containing sufficient oxygen to support life. Do not use this mask when the oxygen concentration is less than 19%.
4. Do not use this mask when concentration of contaminants is high enough to immediately cause danger to health or life.
5. Do not use this mask around explosive materials.
6. Leave work area immediately and return to fresh air if (a) breathing becomes difficult, or (b) dizziness or other distress occurs.
7. Facial hairs or beards and certain facial characteristics may reduce the effectiveness of this mask.
8. Never alter or modify this mask in anyway.
9. Keep masks in the display box away from direct sunlight until use.

STORAGE

- The mask must be stored in their original packaging between -5°C to +50°C temperature.
- Humidity must not be more than 80%.
- Shelf life is 3 years if the above conditions are fulfilled.

SYMBOLS AND PICTOGRAMS

Mfd. under license from:

EyeveX Safety U.S.A., Inc. 1013 Centre Road, Suite 403-B, Wilmington, DE 19805, U.S.A.

www.eyevexsafety.com