

TECHNICAL DATASHEET

EN ISO 20345:2011

EHA 1135 S3 SR | ELA 1136 S3 SR

High Ankle | Low Ankle

EyeveX[®]
Our vision Your safety

Specifications

- Double Density, light weight, DPP PU Sole.
- Upper in Black Barton Grain Buffalo Leather with water repellent properties.
- Rust proof 'D' ring, padded socks, padded ankle
- Imported, soft, breathable and absorbent SPACER lining with antimicrobial treatment for odour control
- Extra wide steel toe cap with 200 Joules impact resistance
- Sole heat resistance - Max 150°C for 60 seconds exposure
- Anti skid, shock absorbent, oil, chemical and fuel resistant outsole.
- Antistatic Shoes
- Comfort Zone insocks
- Steel Mid Plate (Puncture Resistance)
- Heel Height: 35 mm; Toe Height: 27 mm
- Size: 37 - 47



EHA 1135 S3 SR



ELA 1136 S3 SR



200 JOULE
TOECAP



SLIP-
RESISTANT



SHOCK
ABSORPTION



ANTI-NAIL
MIDSOLE



PETROL AND
CHEMICAL
RESISTANT



WATER
RESISTANT



OIL
RESISTANT

Made in India

Mfd. under License from:
EyeveX Safety U.S.A., Inc.

1013 Centre Road, Suite 403-B, Wilmington, DE 19805, U.S.A.

www.eyevexsafety.com