

Schefferville Trading LLC

MANUFACTURER'S TECHNICAL FILE TO THE PPE REGULATION 2016/425

Reference of the product	:	MAXI GRIP CUT 4/C
Article code	:	SGNC 8900
Technical file index	:	01
Last update	:	December 2019

IDENTIFICATION

Reference of the product :	:	MAXI GRIP CUT 4/C
Article code :	:	SGNC 8900
Basic Model		
Technical file index :	:	01
Last update :	:	December 2019

Manufacturer :

Schefferville Trading LLC

Office No.1 Sultan Building, Industrial Area 3 GECO Dubai Road Tablik Markaz
Sharjah,P.O. Box 63934 Sharjah

United Arab Emirates

tel : +971 6 5757860

fax : +971 6 5757890

GLOVE DESCRIPTION

General glove description :

13 GAUGES HIGH DENSITY POLYETHYLENE LINER, MICRO FOAM NITRILE COATING, THUMB CROTCH REINFORCEMENT
type of coating finish : foam

Visual description (picture back and palm sides) :



Field of use

Protective gloves against mechanical risk, used in glass industry; industry; Aerospace, Automotive manufacturing, construction, logistics, packaging, plastic injection molding

Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)			
		Applicable	Covered by
§1	Requirements defined in the Annex II §1 are applicable to all PPE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking
§1.4	Manufacturer's instructions and information is available	<input checked="" type="checkbox"/>	<input type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input type="checkbox"/> Marking
§2.4	If it is known that the design performance of new PPE may be significantly affected by ageing, the month and year of manufacture and/or, if possible, the month and year of obsolescence must be indelibly and unambiguously marked on each item of PPE placed on the market and on its packaging.	<input checked="" type="checkbox"/>	<input type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking
§2.5	PPE which may be caught up during use	<input checked="" type="checkbox"/>	<input type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input type="checkbox"/> Marking
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking
§3.3	The PPE is intended to protect against mechanical injuries	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking

Available sizes :

Minimum length of glove (mm)	Sizes
220mm	6
230mm	7
240mm	8
250mm	9
260mm	10
270mm	11

Glove constitution :

	Reference	Color	Material	Surfacic mass	Gauges	Thickness
Palm		BLACK	NITRILE			0.5-1mm
		BLUE / WHITE	HIGH DENSITY POLYETHYLENE	350g/m2	13	
	thumb crotch reinforcement	BLACK	NITRILE			0.5-1mm
Back		BLUE / WHITE	HIGH DENSITY POLYETHYLENE	350g/m2	13	
Cuff		BLUE / WHITE	HIGH DENSITY POLYETHYLENE/ELASTIC	450g/m2	13	
Binding		Purple / Red / Yellow / Brown / Black / Blue	Polyester			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425.
This glove is designed against mechanical risks.
It is a category II product.

GENERAL REQUIREMENTS

Standard EN 420 : 2003 + A1 : 2009

Dexterity : 5

Size : conform

At the date of certificate the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

Mechanical hazard EN 388 : 2016

Protection offered	Performance levels
Abrasion resistance	4
Blade cut resistance	4
Tear strength resistance	4
Puncture resistance	2
Cut Resistance method (EN ISO 13997)	C
Impact Protection	-

The levels of performance have been measured on the palm

TEST REPORTS

Laboratory	CTC	Other
EN 420 + innocuousness	01222-16 S171114555_1 S171114556_1 S171114558_1 S171114552_1 S171114554_1 S171114557_1 S181216899_1(DMFu)	
EN 388	S170303478_1 01224-16 01223-16	

MARKING - PACKAGING

Information printed on the glove :

Logo of Manufacturer :

Logo 

Glove's reference : MAXI GRIP CUT 4/C

Article Code : SGNC 8900

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Address of Manufacturer :

Date of Manufacture (month/year) and/or Serial number :

Marking example :



Schefferville Trading LLC

**Office No.1 Sultan Building,
Industrial Area 3 GECO Dubai
Road Tablik Markaz
Sharjah, P.O. Box 63934
Sharjah United Arab Emirates**



Method of marking on the glove :

HEAT TRANSFER PRINT AND SEWN LABEL

Packaging :

ONE DOZEN PER BIG POLYBAG, 10DOZEN PER CARTON

PPE subject to ageing :

Peremption period : 3 years when stored in appropriate conditions (humidity, temperature, clean , ventilated, light). Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear, ...).

Declaration of conformity :

Available on : www.eyevexsafety.com

INSTRUCTION FOR USE

Schefferville Trading LLC

Office No.1 Sultan Building, Industrial Area 3 GECO Dubai Road Tablik Markaz Sharjah, P.O. Box 63934 Sharjah

United Arab Emirates

Glove reference : MAXI GRIP CUT 4/C

Article code: SGNC 8900

User notice index : 01

Last update : December 2019

Available sizes : 6 7 8 9 10 11



Schefferville Trading LLC

Office No.1 Sultan Building,
Industrial Area 3 GECO Dubai
Road Tablik Markaz
Sharjah, P.O. Box 63934
Sharjah United Arab Emirates



Glove description :

13 GAUGES HIGH DENSITY POLYETHYLENE LINER, MICRO FOAM NITRILE COATING, THUMB CROTCH REINFORCEMENT

THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the PPE Regulation 2016/425 applicable from April 21th, 2018 : innocuousness, comfort, solidity.

It has been subject to a UE-type Examination performed by :

C.T.C. (OO75)
4, rue Hermann Frenkel
69367 LYON Cedex 07
FRANCE

Applicable standards :

The glove meets the requirements of the standard EN 420 : 2003 + A1 : 2009 « General requirements for work glove ». Dexterity : 5

Moreover, this glove has been designed for the following applications :

Application :

Mechanical hazard - EN 388 : 2016



4 4 4 2 C

Levels of performance

Abrasion resistance	4	(on 4 maxi)
Blade cut resistance	4	(on 5 maxi)
Tear resistance	4	(on 4 maxi)
Puncture resistance	2	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	C	(A to F)
Impact Protection		

Protection limit :

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted.

The levels of performance mentioned are only valid for the palm of the glove.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire

Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear, ...).

For gloves with different layers of material, the performance levels are warranted only for the whole glove.

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

For dulling during the cut resistance test, the coupe test results are only indicative while the TDM cut resistance test is the reference performance result.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

PPE subject to ageing :

Peremption period : 3 years when stored in appropriate conditions (humidity, temperature, clean, ventilated, light). Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear, ...).

Declaration of conformity :

Available on : www.eyevexsafety.com