

TECHNICAL DATASHEET

EYEVEX ESD BOOT



CERTIFICATE OF CONFORMATION - CE certified, EN ISO 20344:2011;
EN ISO 20345:2011 |

Safety Rating - S3 FO E HI WRU HRO SRC

Style - ANKLE-HI SLIP-ON, 9 inches

UPPER: Water Repellent Brown haircell grain Leather

MIDSOLE: Polyurethane | **Outsole:** Rubber

DENSITY – Double, ANTI-TWIST & SHOCK ABSORBENT HEEL, DESIGN
DURABLE DESIGNED TO PREVENT CLOGGING IN SOLE, DIRECT
INJECTION

TOE CAP: Composite toe-cap 200 J, EN 12568:2010

LINING: BREATHABLE, MOISTURE ABSORBENT, SWEAT RESISTANT,
ANTI-BACTERIAL, ANTI-MICROBIAL, ANTI-FUNGAL MATERIAL

PUNCTURE RESISTANT – ANTI PERFORATION KEVLAR

SIZE: EU 38 - 46

OTHER TECHNICAL FEATURES:

ANTI-BACTERIAL, Duracomfort In-Socks

Sole temperature resistance - Max 300° C for 1 minute exposure

SPECIAL FEATURE

ANKLE PROTECTION

ESD 100 K ohms – 35 M ohms

FUEL OIL RESISTANT SOLE

HEAT RESISTANT OUTSOLE (UP TO DEG 300 °C/MIN)

WATER RESISTANT UPPER

ENERGY ABSORBING HEEL

SLIP RESISTANT AGAINST SOAPY CERAMIC/STEEL SURFACES

ABRASION RESISTANT

Weight 750 gms



APPLICATION SECTORS:

Petrochemicals, Oil rigs, Refinery, Marine, Aeronoticals, Waste Management, Railways, Outdoor
Jobs : Wet Area Soft Jobs, Dry Area Soft Jobs



EyeveX
DURA
COMFORT



You can find further information at
www.eyevexsafety.com/products
(or by scanning the QR code).



Mfd. under License from:
EyeveX Safety U.S.A INC.,
1013 Centre Road, Suite 403-B
Wilmington, DE 19805, U.S.A

www.Eyevexsafety.com