

RETRACTABLE BLOCK POLYMER CASING WITH G.I. WIRE ROPE WITH INBUILT

ESRL - 30

Robust, light weight and Durable Polymer casing made from high impact strength nylon. Has a Swivel Anchorage eye at one end: and a Swivel Steel Snap Hook ESF -1404 at the retractable end.

DESIGN

Quick activating breaking mechanism component
Robust & durable plastic casing
Has swivel anchorage eye at anchorage end
Steel snap hook at retractable end (Our ref. ESF-1404 as per ANSI Z359.12-2009 & EN 362:2002 gate strength 3600 lbs. Galvanized steel wire rope (option of having S.S. wire rope available)

LENGTH

30 mtr

CABLE

Material: Galvanized steel wire dia 4.5 mm.
Minimum Breaking Strength: 12 KN

WEIGHT

ESRL -30 :- 12.680 kg \pm 0.100 kg


USER CAPACITY

User Capacity: 140 kg Max.

RELEVANT STANDARD

Meets or Exceeds EN 360 : 2002

CE **ANSI** Z359.14 2021



Mfd. under License from:
800 N King Street, Suite 304 1825
Wilmington, DE 19801, USA
www.eyevexsafety.com
Made in India



You can find further information at
www.eyevexsafety.com/products
(or by scanning the QR code).